

# SU1Y

**SINTERED GLASS JUNCTION  
FAST SWITCHING PLASTIC RECTIFIER**  
VOLTAGE:1600V      CURRENT: 0.5A




## FEATURE

High temperature metallurgic ally bonded construction  
Sintered glass cavity free junction  
Capability of meeting environmental standard of MIL-S-19500  
High temperature soldering guaranteed  
350°C/10sec at 5 lbs tension  
Operate at Ta =55°C with no thermal run away  
Typical Ir<0.2µA

## MECHANICAL DATA

Terminal: Plated leads solderable per J-STD-002  
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy  
Polarity: color band denotes cathode  
Mounting position: any



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	SU1Y	units
Maximum Recurrent Peak Reverse Voltage	V <sub>rrm</sub>	1600	V
Maximum RMS Voltage	V <sub>rms</sub>	1120	V
Maximum DC blocking Voltage	V <sub>dc</sub>	1600	V
Minimum Reverse Breakdown Voltage IR = 100µA	V(BR) <sub>R</sub>	1650	V
Maximum Average Forward Rectified Current	I <sub>f(av)</sub>	0.5	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I <sub>fsm</sub>	15	A
Maximum Forward Voltage at 0.5A and 25°C	V <sub>f</sub>	3.6	V
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	I <sub>r</sub>	5.0 200.0	µA µA
Maximum Reverse Recovery Time (Note 1)	T <sub>rr</sub>	75	nS
Typical Junction Capacitance (Note 2)	C <sub>j</sub>	5.0	pF
Typical Thermal Resistance (Note 3)	R <sub>th(ja)</sub>	65.0	°C/W
Storage and Operating Junction Temperature	T <sub>stg</sub> , T <sub>j</sub>	-65 to +175	°C

### Note:

- Reverse Recovery Condition I<sub>f</sub> =0.5A, I<sub>r</sub> =1.0A, I<sub>rr</sub> =0.25A
- Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
- Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

## RATINGS AND CHARACTERISTIC CURVES SU1Y

