

31DF2

**ULTRAFAST EFFICIENT
GLASS PASSIVATED RECTIFIER**
VOLTAGE: 200V CURRENT: 3.0A




FEATURE

Low power loss
High surge capability
Ultra-fast recovery time for high efficiency
High temperature soldering guaranteed
250°C/10sec/0.375" lead length at 5 lbs tension

MECHANICAL DATA

Terminal: Plated axial leads solderable per
MIL-STD 750, method 2026
Case: Molded with UL-94 Class V-0 recognized Flame
Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO-201AD



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	31DF2	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	200	V
Maximum RMS Voltage	Vrms	140	V
Maximum DC blocking Voltage	Vdc	200	V
Maximum Average Forward Rectified Current, 0.375" lead length at TL =110°C	If(av)	3.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	80	A
Maximum Forward Voltage at Forward current At3.0A (Note 1)	Vf	0.98	V
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =120°C	Ir	10.0 100.0	μ A μ A
Maximum Reverse Recovery Time (Note 2)	Trr	30	nS
Typical Thermal Resistance	R(ja)	30.0	°C/W
Storage and Operating Junction Temperature	Tstg,Tj	-40 to +150	°C

Note:

1. Pulse test:300uS pulse width, 1% duty cycle
2. Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A

Fig. 1 – Maximum Forward Current Derating Curve




Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 – Typical Reverse Current




Fig. 4 – Typical Forward Voltyage




Fig. 5 – Typical Junction Capacitance

