


SOD-323 SURFACE MOUNT


Flat Lead Plastic Package

Schottky Barrier Diode

Green Product



SOD-323 Flat Lead



Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
P_D	Power Dissipation	250	mW
T_{STG}	Storage Temperature Range	-55 to +125	$^\circ\text{C}$
T_J	Junction Temperature	+125	$^\circ\text{C}$
V_{RM}	Repetitive Peak Reverse Voltage	40	V
I_O	Average Rectified Output Current	1	A
I_{FSM}	Peak Forward Surge Current ($t=8.3\text{ms}$ Single Half Sine-wave)	9	A
I_{FRM}	Repetitive Peak Forward Current	1.5	A

These ratings are limiting values above which the serviceability of the diode may be impaired.

Specification Features:

- RoHS Compliant
- Green EMC
- Matte Tin(Sn) Lead Finish
- Band Indicates Cathode
- Weight: approx. 0.004g



DEVICE MARKING CODES:

Device Type	Device Marking
B5819WS	SL


Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Limits			Unit
			Min	Typ	Max	
V_{BR}	Reverse Breakdown Voltage	$I_R=1\text{mA}$	40	--	--	Volts
I_R	Reverse Leakage Current	$V_R=40\text{V}$	--	--	1	mA
V_F	Forward Voltage	$I_F=1\text{A}$	--	--	0.60	Volts
C_d	Diode Capacitance	$V_R=4\text{V}$, $f=1\text{MHz}$	--	30	--	pF

RATING AND CHARACTERISTIC CURVES



SOD-323 Package Outline



NOTES:

1. The above package outline is similar to JEITA SC-90.
 2. Dimensions are exclusive of Burrs, Mold Flash & Tie Bar extrusions.
-



NOTICE

The information presented in this document is for reference only. VolarisTech reserves the right to make changes without notice for the specification of the products displayed herein.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), VolarisTech Inc., or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <https://www.volaristech.com/>, or consult your nearest VolarisTech's sales office for further assistance.