

ERA10JEGF

**SINTERED GLASS JUNCTION
FAST SWITCHING PLASTIC RECTIFIER**
VOLTAGE:600 CURRENT: 1.0A




FEATURE

High temperature metallurgically bonded construction
Sintered glass cavity free junction
Capability of meeting environmental standard of MIL-S-19500
High temperature soldering guaranteed
350°C /10sec/0.375"lead length at 5 lbs tension
Operate at Ta =55°C with no thermal run away
Typical Ir<0.2μA
Low power loss, high efficient

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

| | SYMBOL | ERA 10J EGF | units |
|---|----------|-------------|----------|
| Maximum Recurrent Peak Reverse Voltage | Vrrm | 600 | V |
| Maximum RMS Voltage | Vrms | 420 | V |
| Maximum DC blocking Voltage | Vdc | 600 | V |
| Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C | If(av) | 1.0 | A |
| Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load | I fsm | 30 | A |
| Maximum Forward Voltage at Forward Current 0.5A and 25°C | Vf | 1.5 | V |
| Maximum full load reverse current full cycle average at 55°C Ambient | Ir(av) | 50 | μA |
| Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =125°C | Ir | 10 50 | μA μA |
| Maximum Reverse Recovery Time (Note 1) | Trr | 75 | nS |
| Typical Junction Capacitance (Note 2) | Cj | 17 | pF |
| Typical Thermal Resistance (Note 3) | R(ja) | 50 | °C/W |
| Storage and Operating Temperature Range | Tstg, Tj | -65 to +175 | °C |

Note:

1. Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A
2. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
3. Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

RATINGS AND CHARACTERISTIC CURVES ERA10JEGF

FIG. 1 - MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

