

GSIB15A80-70A

SINGLE PHASE GLASS PASSIVATED BRIDGE RECTIFIER

Voltage: 800V

Current: 15.0A




Features

Glass passivated chip junction
Ideal for printed circuit board
High surge current capability
High case dielectric strength
This series is UL listed under Recognized Component Index, file number E330278

Mechanical Data

Terminal: Plated leads solderable per J-STD-002
Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: Polarity symbol marked on body
Mounting position: any

GSIB-5S



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60Hz, resistive or inductive load rating at 25°C, unless otherwise stated,)

	Symbol	GSIB15A80-70A	units
Maximum repetitive peak reverse voltage	V _{rrm}	800	V
Maximum RMS voltage	V _{rms}	560	V
Maximum DC blocking voltage	V _{dc}	800	V
Maximum average forward Rectified output current at T _c =100°C (with heatsink) Ta=25°C (without heatsink)	I _{f(av)}	15.0 3.2	A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	I _{fsm}	200	A
Maximum instantaneous forward voltage drop per leg at 7.5A	V _f	1.1	V
Rating for fusing (t < 8.3ms)	I ² t	110	A ² Sec
Maximum DC reverse current at rated DC blocking voltage per leg	I _r	10 250	μA
Maximum thermal resistance per leg	(Note1) R _{th(ja)} (Note2) R _{th(jc)} (Note3) R _{th(jl)}	22 1.5 5	°C/W
Operating junction and storage temperature range	T _j , T _{stg}	-55 to +150	°C

Note:

1. Junction to Ambient without heatsink
2. Junction to Case with heatsink
3. Junction to Lead without heatsink
4. Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with #6 screw

RATINGS AND CHARACTERISTIC CURVES GSIB15A80-70A




Figure 1. Derating Curve Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 3. Typical Forward Characteristics Per Leg




Figure 4. Typical Reverse Characteristics Per Leg




Figure 5. Typical Junction Capacitance Per Leg