

GSIB4A05 THRU GSIB4A100

SINGLE PHASE GLASS PASSIVATED BRIDGE RECTIFIER

Voltage: 50 to 1000V

Current: 4.0A




Features

Glass passivated chip junction
Ideal for printed circuit board
High surge current capability
High case dielectric strength
This series is UL listed under Recognized Component Index, file number E330278

Mechanical Data

Terminal: Plated leads solderable per J-STD-002
Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: Polarity symbol marked on body
Mounting position: any

GSIB-3S



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

| | Symbol | GSIB4 A05 | GSIB4 A10 | GSIB4 A20 | GSIB4 A40 | GSIB4 A60 | GSIB4 A80 | GSIB4 A100 | units | |
|---|--|--------------|--------------|--------------|--------------|--------------|--------------|---------------|-------|--------------------|
| Maximum repetitive peak reverse voltage | V _{rrm} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | |
| Maximum RMS voltage | V _{rms} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V | |
| Maximum DC blocking voltage | V _{dc} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | |
| Maximum average forward Rectified output current at T _c = 100°C (Note 1) Ta = 25°C (Note 2) | I _{f(av)} | 4.0 | | | | | | | | A |
| Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method) | I _{fsm} | 80 | | | | | | | | A |
| Maximum instantaneous forward voltage drop per leg at 2.0A | V _f | 1.0 | | | | | | | | V |
| Rating for fusing (t < 8.3ms) | I ² t | 32 | | | | | | | | A ² Sec |
| Maximum DC reverse current at Ta = 25°C rated DC blocking voltage per leg Ta = 125°C | I _r | 5.0 | | | | | | | | μA |
| Maximum thermal resistance per leg (Note2) (Note1) | R _{th(ja)} R _{th(jc)} | 26.0 | | | | | | | | °C/W |
| Operating junction and storage temperature range | T _j , T _{stg} | -55 to +150 | | | | | | | | °C |

Note:

- Unit case mounted onAl plate heatsink
- Unit case mounted on P.C.B. with 0.5 x 0.5" (12 x 12mm) copper pads and 0.375"(9.5mm) lead length
- Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with #6 screw

RATINGS AND CHARACTERISTIC CURVES GSIB4A05 THRU GSIB4A100




Figure 1. Derating Curve Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 3. Typical Forward Characteristics Per Leg




Figure 4. Typical Reverse Characteristics Per Leg




Figure 5. Typical Junction Capacitance Per Leg




Figure 6. Typical Transient Thermal Impedance Per Leg