

UG2D-A

ULTRAFAST EFFICIENT PLASTIC SILICON RECTIFIER

VOLTAGE : 200V

CURRENT : 2.0A




FEATURE

Low power loss
High surge capability
Glass passivated chip junction
Ultra-fast recovery time for high efficiency
High temperature soldering guaranteed
250 /10sec/0.375 lead length at 5 lbs tension

MECHANICAL DATA

Terminal : Plated axial leads solderable per
MIL-STD 202E, method 208C
Case : Molded with UL-94 Class V-0 recognized Flame
Retardant Epoxy
Polarity : color band denotes cathode
Mounting position : any

DO-41/DO-204AL



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60HZ, resistive or inductive load rating at 25 °C, unless otherwise stated)

	SYMBOL	UG2D-A	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	200	V
Maximum RMS Voltage	V _{rms}	140	V
Maximum DC blocking Voltage	V _{dc}	200	V
Maximum Average Forward Rectified Current 3/8 lead length at T _a =75	I _{f(av)}	2.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	80.0	A
Maximum Forward Voltage at Forward current 2.0A Peak	V _f	0.95	V
Maximum DC Reverse Current T _a =25 at rated DC blocking voltage T _a =120	I _r	5.0 200.0	μ A μ A
Maximum Reverse Recovery Time (Note 1)	T _{rr}	15	nS
Typical Junction Capacitance (Note 2)	C _j	15	pF
Typical Thermal Resistance (Note 3)	R(ja)	45	/W
Storage and Operating Junction Temperature	T _{stg} ,T _j	-55 to +150	

Note :

1. Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A
2. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
3. Thermal Resistance from Junction to Ambient at 3/8 lead length, P.C. Board Mounted

FIG. 1 - MAXIMUM FORWARD CURRENT DERATING CURVES




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS




FIG. 5 - REVERSE SWITCHING CHARACTERISTICS




FIG. 6 - TYPICAL JUNCTION CAPACITANCE

