

UG6KB05 THRU UG6KB100

SINGLE PHASE GLASS PASSIVATED BRIDGE RECTIFIER

Voltage: 50 to 1000V

Current: 6.0A




Features

Glass passivated chip junction
High case dielectric strength
High surge current capability
Ideal for printed circuit board
This series is UL listed under Recognized Component Index, file number E330278

Mechanical Data

Terminal: Plated leads solderable per J-STD-002
Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: Polarity symbol marked on body
Mounting position: any




MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)


	Symbol	UG6K B05	UG6 KB10	UG6 KB20	UG6 KB40	UG6K B60	UG6 KB80	UG6K B100	units
Maximum repetitive peak reverse voltage	V _{rrm}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{rms}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{dc}	50	100	200	400	600	800	1000	V
Maximum average forward rectified output current T _c 138°C with heatsink	I _{f(av)}	6.0							A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	I _{fsm}	150							A
Maximum instantaneous forward voltage drop per leg at 3.0A	V _f	1.00							V
Rating for fusing (3ms ≤ t < 8.3ms)	I ² t	93							A ² Sec
Maximum DC reverse current at rated DC blocking voltage per leg	I _r	10.0 500							μA
Thermal resistance	R _{th(ja)} R _{th(jc)} R _{th(jl)}	55 1.5 15							°C/W
Operating junction and storage temperature range	T _j , T _{stg}	-55 to +150							°C

Note:

RATINGS AND CHARACTERISTIC CURVES UG6KB05 THRU UG6KB100



**Fig. 1 – Derating Curve
Output Rectified Current**



**Fig. 2 – Maximum Non-Repetitive Peak
Forward Surge Current Per Leg**




Figure 3. Typical Forward Characteristics Per Diode




Figure 4. Typical Reverse Leakage Characteristics Per Diode




Figure 5. Typical Junction Capacitance Per Diode